

YK 系列摇摆式制粒机

YK Series Scilating Granulator

性能概述：

本机用以将潮湿的粉料研制成所需的颗粒，也可以将块状的干料粉碎至所需的颗粒。主要特点是在研制颗粒时，旋转滚筒的转速可以调节。筛网拆装简易，还可适当调节松紧。机械传动系统全部封闭在机体内，并附有自动润滑系统，提高了机件的寿命。

Applications:

The machine is used for forming the required granules from moist power material, or for crushing dried block stock into granules in required size. Its main features are: the rotating speed of the rotor can be adjusted during operation and the sieve can be removed and remounted easily; its tension also adjustable. The driving mechanism is totally enclosed in the machine body and its lubrication system improves the lifetime of the mechanical components.

技术参数 Technical Parameters:

参数 ITEM		型号 TYPE		
		YK60	YK90	YK160
滚筒直径 Dia. Of Roller	mm	60	90	160
滚筒有效长度 Effective Length Of Roller	mm	184	290	360
滚筒转速 Roller Speed	r/min	50		
生产能力 Production Capacity	kg/h	20-25	40-50	300-700
额定功率 Rated Motor	kw	0.37	0.37	2.2
外形尺寸 Overall Size	mm	530*400*530	700*400*780	910*700*1200
机器净重 Net Weight	kg	70	100	280



ZL 系列旋转式颗粒机

ZL Series Rotary Granulator

性能概述：

本机是通过一组旋转碾刀，将前道工序制成的湿材注入环碾刀的不锈钢筛筒筛孔中，从而制成圆柱状的湿颗粒，供下道工序抛丸使用。本设备可通过更换不锈钢筛筒来取得不同大小的颗粒。制湿颗粒也可根据物料和所需球形颗粒的大小。

Applications:

This machine adopts one pair of rotating grinding blade to grind form damp material into column-shape granule by stainless steel sieve cylinder which is provided to pelletize in next process. The machine can obtain different size granule by changing the stainless steel sieve. The machine is mainly suitable for pharmaceutical industry, foodstuff industry, chemical industry, and so on. It can make the stirred raw material granulate the needed granule.

技术参数 Technical Parameters:

参数 ITEM	型号 TYPE		
	ZL250A	ZL300B	ZL300D
筛筒直径 Dia. of Sieve Tube	250 mm	300 mm	300mm
筛筒孔径 Dia. of Sieve Holes	0.8-2.5 mm	0.8-3 mm	0.5-2.5 mm
生产能力 Production Capacity	60-200 kg/h	140-400	300-600
碾刀速度 Rotation Rate of Rolling Knives	60 r/min	70 r/min	80 r/min
电机功率 Motor	3 kw	4Kw	7.5Kw
外形尺寸 Overall Size	700*500*1450 mm	880*640*1300	1300*800*1200
机器净重 Net Weight	350 kg	400	780

